

Final disposal of SABROE refrigeration equipment

Safety precautions

Danger!

Before dismantling the plant, read the safety precautions carefully.

Dismantling a refrigeration unit to be scrapped must be carried out safely.

Only competent refrigeration personnel must perform the dismantling as fundamental knowledge of refrigeration systems and the risks involved are required.

Before dismantling the unit, refrigerant and oil must be drained into suitable containers. Disconnect all electrical connections to the unit and remove fuses in the main switchboard.

During the dismantling process, the individual machine parts and components must be sorted to ensure proper disposal. Hazardous waste must be handled at a site complying with the prevailing national rules and regulations.

Danger!

Be very careful when using cutting tools, such as angle grinders or flame cutters, during the dismantling process, as pipes and the like contain oil residue and refrigerant, which may be toxic and/or flammable.

Waste disposal

Machine parts

When dismantling the plant, it is important to properly sort the parts that should be disposed of. The compressor, frame, containers and so on belonging to the category of iron and metal scrap must be brought to an approved scrap dealer who complies with the prevailing national rules and regulations.

Oil and refrigerant

Oil and refrigerant waste must be disposed of in accordance with the prevailing national rules and regulations. Do not transport oil in open containers in a closed car.

Electric components

Electric and electronic products such as wiring, panels and hardware must be disposed of in accordance with prevailing national rules and regulations.

Batteries

Used batteries, for example from the control system backup, must be disposed of in accordance with prevailing national rules and regulations.