



SABrecip



SMC 116 single-beam reciprocating compressor unit with UniSAB systems controller

Sabroe SMC reciprocating compressor units

Large single-stage compressors with swept volumes of 200–1,350 m³/h

SMC compressor units are ideal for use in medium-sized refrigeration installations where reliable service is a major priority. They are particularly effective under part-load conditions.

Sabroe SMC compressors are world-renowned for their exceptional reliability, making them an economical, low-maintenance solution for heavy-duty refrigeration, using all common refrigerants. Our three-year warranty covers the complete unit, including compressor block, UniSAB, motor and coupling – for all refrigerants.

Range

Fifteen different models are available to provide swept volumes of between 200 and 1,350 m³/h.

Advantages	Benefits
High coefficient of performance (COP), with excellent performance under part-load conditions	Low power consumption, which greatly reduces operating costs
Variable-speed drive provides stepless capacity control over the entire operating range	Power consumption and operating costs kept to a minimum
Condition-based service intervals embedded in the controls equipment	Minimum downtime and low service costs due to extremely long service intervals
Easy to access for service, with limited spare parts requirements	Easy, inexpensive maintenance, which helps limit downtime and reduce operating costs
Optional special oil separator design based on coalescer technology	Low oil carry-over, which cuts back on oil costs
Configured without oil system	Small footprint and easy service access



Technical data

Model	Number of cylinders	Swept volume		Nominal capacities * in kW at 1500 rpm			Nominal capacities * in kW at 1800 rpm			Unit dimensions in mm			Weight excluding motor	Sound pressure level	
		1500 rpm	1800 rpm	Single/high-stage		Booster	Single/high-stage		Booster					1500 rpm	1800 rpm
		m ³ /h	m ³ /h	-10/+35°C	0/+40°C	-40/-10°C	-10/+35°C	0/+40°C	-40/-10°C	L	W	H	kg	db(A)	db(A)
SMC 104 S	4	226	271	127	195	35	153	235	42	2261-2865	1213	1229	1195	79	82
SMC 104 L	4	283	339	165	250	47	198	300	57	2261-2865	1213	1229	1215	80	83
SMC 104 E	4	339	N/A	203	306	58	N/A	N/A	N/A	2261-2865	1213	1229	1220	80	83
SMC 106 S	6	339	407	191	293	53	229	352	64	2286-2890	1267	1247	1380	81	83
SMC 106 L	6	424	509	247	375	71	297	450	85	2286-2890	1267	1247	1400	82	84
SMC 106 E	6	509	N/A	304	459	87	N/A	N/A	N/A	2286-2890	1267	1247	1410	82	84
SMC 108 S	8	452	543	255	391	71	306	469	85	2311-2915	1361	1247	1595	82	84
SMC 108 L	8	566	679	330	500	94	396	600	113	2311-2915	1361	1247	1630	83	85
SMC 108 E	8	679	N/A	406	612	116	N/A	N/A	N/A	2311-2915	1361	1247	1650	83	85
SMC 112 S	12	679	814	382	586	106	459	703	127	3279-3687	1475	1448	2255	83	85
SMC 112 L	12	848	1018	495	750	141	593	900	169	3279-3687	1475	1448	2280	83	86
SMC 112 E	12	1018	N/A	609	918	173	N/A	N/A	N/A	3279-3687	1475	1448	2330	83	86
SMC 116 S	16	905	1086	510	782	141	611	938	170	3329-3737	1536	1445	2505	84	86
SMC 116 L	16	1131	1357	659	1000	188	791	1200	226	3329-3737	1536	1445	2535	84	87
SMC 116 E	16	1357	N/A	812	1224	231	N/A	N/A	N/A	3329-3737	1536	1445	2590	84	87

Dimensions, weight and sound pressure levels are guidelines only.

Options

- UniSAB systems controller
- Variable-speed drive line (UniSAB always included)
- Oil separator for low oil carry-over
- Gauges, thermometers and temperature/pressure control switches
- Extended cylinder capacity control
- Oil level regulator (for use in parallel systems)
- ATEX-compliant configuration
- Special vibration dampening

Min./max. speed	R717
SMC S	500-1800 rpm
SMC L	500-1800 rpm
SMC E	500-1500 rpm

* Nominal capacities are based on:

1500 rpm at 50 Hz.
1800 rpm at 60 Hz or VSD.

Refrigerant: R717
Other refrigerants available on request.

For R717

2K liquid subcooling and 0.5K non-usable suction superheat.

Design pressure, HP side: 28 bar
Design pressure, LP side: 18 bar
Differential pressure: 21 bar

Sound pressure levels measured in free field, over reflecting plane and one metre distance from the compressor block.